

# SUNFIRE®

## THE ULTIMATE RADIANT HEATERS

# HEATERS



  
**QUIET**

  
**SAFE**

  
**CLEAN**

WATCH VIDEO



# NO SMELL NO FUMES



SPECIFICATIONS	SF80	SF120	SF150
<b>BTU/Hour:</b>	80,000	120,000	High 150,000, Low 130,000
<b>Fuel Types:</b>	Diesel, Kerosene, #2 Fuel Oil	Diesel, Kerosene, #2 Fuel Oil	Diesel, Kerosene, #2 Fuel Oil
<b>Fuel Tank Capacity:</b>	6 Gallons	14 Gallons	19 Gallons
<b>Flow Rate (GPH):</b>	.58 for Diesel .56 for Kerosene	.85 GPH for Diesel .78 GPH for Kerosene	High: 1.10 GPH, Low: .97 GPH
<b>Run Time (Approx.):</b>	10 Hrs.	16 Hrs.	High: 17 Hrs., Low 19 Hrs.
<b>Dimensions:</b>	19.75"W x 26"L x 27.75"H	28.5"W x 32"L x 33.75"H	24.4"W x 36"L x 40.8"H
<b>Dry Weight:</b>	85 lbs.	120 lbs.	193 lbs.
<b>Wet Weight (Full Tank):</b>	132 lbs.	210 lbs.	318 lbs.
<b>Electrical:</b>	120V .5A 60HZ 12V Pure Sine Power Inverter (800W Minimum)	120V 1.2A 60HZ 12V Pure Sine Power Inverter (800W Minimum)	120V 2A 60HZ 12V Pure Sine Power Inverter (800W Minimum)

## COMMON APPLICATIONS

 <b>CONSTRUCTION</b>	 <b>AUTO SHOPS</b>	 <b>FARMS</b>	 <b>GARAGE</b>
 <b>SPORTS</b>	 <b>EVENTS</b>	 <b>JOBSITE</b>	 <b>POLE BARN</b>



### THERMOSTAT OPTION:

All models can be regulated with any standard mechanical or battery-operated wall thermostat. Thermostat not included.

### CALIFORNIA PROP 65

This product can expose you to ceramic fibers, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

- Not for indoor household residential use.
- Proper ventilation required.

